



BFL916

- Good Handling.
- Low rolling resistance.



Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load and Inflated Pressure		Inflated Overall Diameter (mm)	Inflated Section Width (mm)	Pattern Depth (mm)	Pattern	Operative Norm
					Dual(Kg/Kpa)	Single(Kg/Kpa)					
9.00R20	16	144/142	K	70	2650/900	2800/900	1019	259	15.0	BFL916	GB
10.00R20	16	146/143	L	75	2750/830	3000/830	1054	278	16.0	BFL916	TRA
11.00R20	16	150/147	L	80	3075/830	3350/830	1085	293	16.0	BFL916	GB
11.00R20	18	152/149	L	80	3250/930	3550/930	1085	293	16.0	BFL916	GB
11R22.5	14	144/142	M	825	2650/720	2800/720	1054	279	15.0	BFL916	TRA
11R22.5	16	146/143	M	825	2725/830	3000/830	1054	279	15.0	BFL916	TRA
11R24.5	14	146/143	M	825	2725/720	3000/720	1104	279	15.0	BFL916	TRA
11R24.5	16	149/146	M	825	3000/830	3250/830	1104	279	15.0	BFL916	TRA
12.00R20	18	154/151	L	85	3450/830	3750/830	1125	315	16.0	BFL916	TRA
12R22.5	16	150/147	M	900	3075/830	3350/830	1085	300	16.5	BFL916	GB
285/75R24.5	14	144/141	M	825	2575/760	2800/760	1050	283	15.0	BFL916	TRA
285/75R24.5	16	147/144	M	825	2800/830	3075/830	1050	283	15.0	BFL916	TRA
295/75R22.5	14	144/141	M	900	2575/760	2800/760	1014	298	15.0	BFL916	TRA
295/75R22.5	16	146/143	M	900	2725/830	3000/830	1014	298	15.0	BFL916	TRA





BDL937

- Suitable for the drive axle of the trucks running on highway.
- Good braking and grip on wet road.
- Long life.



Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load and Inflated Pressure		Inflated Overall Diameter (mm)	Inflated Section Width (mm)	Pattern Depth (mm)	Pattern	Operative Norm
					Dual(Kg/Kpa)	Single(Kg/Kpa)					
10.00R20	16	146/143	K	7.50	2725/830	3000/830	1054	278	20.5	BDL937	GB
10.00R20	18	149/146	K	7.50	3000/930	3250/930	1054	278	20.5	BDL937	GB
11R22.5	14	144/142	M	8.25	2650/720	2800/720	1065	279	20.5	BDL937	TRA
11R22.5	16	146/143	M	8.25	2725/830	3000/830	1065	279	20.5	BDL937	TRA
11R24.5	14	146/143	M	8.25	2725/720	3000/720	1116	279	20.5	BDL937	TRA
11R24.5	16	149/146	M	8.25	3000/830	3250/830	1116	279	20.5	BDL937	TRA
265/70R19.5	18	143/141	J	7.50	2575/850	2725/850	867	262	16.5	BDL937	ETRTO
285/75R24.5	14	144/141	M	8.25	2575/760	2800/760	1056	283	20.5	BDL937	TRA
285/75R24.5	16	147/144	M	8.25	2800/830	3075/830	1056	283	20.5	BDL937	TRA
295/75R22.5	14	144/141	M	9.00	2575/760	2800/760	1020	298	20.5	BDL937	TRA
295/75R22.5	16	146/143	M	9.00	2725/830	3000/830	1020	298	20.5	BDL937	TRA





BAM908

- Typical combined pattern.
- Suitable for trucks of different tonnages which run on highway and normal road.
- Strong wear resistance, low heat generation.
- Good handling.



Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load and Inflated Pressure		Inflated Overall Diameter (mm)	Inflated Section Width (mm)	Pattern Depth (mm)	Pattern	Operative Norm
					Dual(Kg/Kpa)	Single(Kg/Kpa)					
6.50R16LT	10	107/102	M	5.50F	850/560	975/560	750	185	11.0	BAM908	GB
6.50R16LT	12	110/105	L	5.50F	925/670	1060/670	750	185	11.0	BAM908	GB
7.00R16LT	12	115/110	M	5.50F	1060/670	1215/670	775	200	12.0	BAM908	GB
7.00R16LT	14	117/116	L	5.50F	1250/700	1285/700	775	200	12.0	BAM908	/
7.00R16LT	14	118/114	L	5.50F	1180/770	1320/770	775	200	12.0	BAM908	GB
7.50R16LT	12	120/116	M	6.00G	1250/670	1400/670	805	215	13.0	BAM908	GB
7.50R16LT	14	122/118	M	6.00G	1320/770	1500/770	805	215	13.0	BAM908	GB
7.50R20	12	128/126	L	6.00	1700/760	1800/760	935	215	14.0	BAM908	GB
7.50R20	14	130/128	K	6.00	1800/830	1900/830	935	215	14.0	BAM908	GB
8.25R16LT	14	128/126	K	6.50H	1700/675	1800/675	855	235	14.0	BAM908	/
8.25R16LT	12	123/119	M	6.50H	1360/560	1550/560	855	235	14.0	BAM908	GB
8.25R16LT	14/14+	126/122	L	6.50H	1500/670	1700/670	855	235	14.0	BAM908	GB
8.25R16LT	16	128/124	L	6.50H	1600/770	1800/770	855	235	14.0	BAM908	GB
8.25R20	12	133/131	L	6.50	1950/720	2060/720	974	236	16.0	BAM908	GB
8.25R20	14	136/134	L	6.50	2120/830	2240/830	974	236	16.0	BAM908	GB
8.25R20	16	139/137	L	6.50	2300/930	2430/930	974	236	16.0	BAM908	GB
9.00R20	14	141/139	K	7.00	2430/790	2575/790	1019	259	15.5	BAM908	TRA
9.00R20	16	144/142	K	7.00	2650/900	2800/900	1019	259	15.5	BAM908	GB
10.00R20	16	146/143	K	7.50	2725/830	3000/830	1054	278	16.0	BAM908	TRA
10.00R20	18	149/146	K	7.50	3000/930	3250/930	1054	278	16.0	BAM908	GB
11.00R20	16	150/147	K	8.00	3075/830	3350/830	1085	293	17.0	BAM908	GB
11.00R20	18	152/149	K	8.00	3250/930	3550/930	1085	293	17.0	BAM908	TRA
11R22.5	14	144/142	K	8.25	2650/720	2800/720	1054	279	16.0	BAM908	TRA
11R22.5	16	146/143	K	8.25	2725/830	3000/830	1054	279	16.0	BAM908	TRA
11R24.5	14	146/143	K	8.25	2725/720	3000/720	1104	279	16.0	BAM908	TRA
11R24.5	16	149/146	K	8.25	3000/830	3250/830	1104	279	16.0	BAM908	TRA
12.00R20	18	154/151	K	8.50	3450/830	3750/830	1125	315	17.5	BAM908	TRA
12R22.5	16	152/148	K	9.00	3150/830	3550/830	1084	300	17.5	BAM908	ETRTO
12.00R24	18	156/153	K	8.50	3650/775	4000/775	1226	313	17.5	BAM908	ETRTO
12.00R24	20	160/156	K	8.50	4000/850	4500/850	1226	313	17.5	BAM908	ETRTO
315/80R22.5	18	154/150	M	9.00	3350/825	3750/825	1076	312	17.5	BAM908	ETRTO
315/80R22.5	20	156/150	L	9.00	3350/850	4000/850	1076	312	17.5	BAM908	ETRTO
12R24.5	16	152/149	K	9.00	3250/830	2550/830	1135	300	16.5	BAM908	TRA
12R24.5	18	154/151	K	9.00	3450/930	3750/930	1135	300	16.5	BAM908	GB



BAM938

- Suitable for the drive axle of the trucks running on highway.
- Good braking and grip on wet road.
- Long life.



Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load and Inflated Pressure		Inflated Overall Diameter (mm)	Inflated Section Width (mm)	Pattern Depth (mm)	Pattern	Operative Norm
					Dual(Kg/Kpa)	Single(Kg/Kpa)					
385/55R22.5	18	158	L	12.25	/	4250/850	996	386	17.0	BAM938	ETRTO
385/55R22.5	20	160	J	12.25	/	4500/900	996	386	17.0	BAM938	ETRTO
385/55R22.5	18	158	K	11.75	/	4250/850	1072	389	17.0	BAM938	ETRTO
385/65R22.5	20	160	J	11.75	/	4500/900	1072	389	17.0	BAM938	ETRTO
425/65R22.5	18	162	K	12.25	/	4750/760	1124	422	18.0	BAM938	ETRTO
425/65R22.5	20	165	J/K	13.00	/	5150/825	1124	430	18.0	BAM938	ETRTO
445/65R22.5	20	168	J/K	13.00	/	5600/830	1150	444	18.5	BAM938	TRA
445/65R22.5	20	169	J	14.00	/	5800/900	1150	444	18.5	BAM938	ETRTO





BFL902

- Special for trucks of different tonnages which run on highway.
- Suitable and safe when run on wet and slippery road.
- Low fuel consumption.



Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load and Inflated Pressure		Inflated Overall Diameter (mm)	Inflated Section Width (mm)	Pattern Depth (mm)	Pattern	Operative Norm
					Dual(Kg/Kpa)	Single(Kg/Kpa)					
9.00R20	14	141/139	L	7.00	2430/790	2575/790	1019	259	14.5	BFL902	TRA
9.00R20	16	144/142	L	7.00	2650/900	2800/900	1019	259	14.5	BFL902	GB
10.00R20	16	146/143	M	7.50	2725/830	3000/830	1054	278	16.0	BFL902	TRA
10.00R20	18	149/146	L	7.50	3000/930	3250/930	1054	293	16.0	BFL902	GB
11.00R20	16	150/147	L	8.00	3075/830	3350/830	1085	293	16.0	BFL902	GB
11.00R20	18	152/149	L	8.00	3250/930	3550/930	1085	293	16.0	BFL902	TRA
12.00R20	18	154/151	L	8.50	3450/830	3750/830	1125	315	16.5	BFL902	TRA
12R22.5	16	152/148	L	9.00	3150/850	3550/850	1084	300	15.0	BFL902	ETRTO
13R22.5	18	156/150	K	9.75	3350/875	4000/875	1124	320	17.0	BFL902	ETRTO
295/80R22.5	16	150/147	M	9.00	3075/830	3350/830	1044	298	15.0	BFL902	GB
295/60R22.5	16	149/146	M	9.00	3000/900	3250/900	926	292	15.0	BFL902	ETRTO
315/80R22.5	18	154/150	M	9.00	3350/825	3750/825	1076	312	15.0	BFL902	ETRTO
315/80R22.5	20	156/150	L	9.00	3350/850	4000/850	1076	312	15.0	BFL902	ETRTO





BFL986

■ Suitable for all position of buses and medium trucks running on the high-grade road.



Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load and Inflated Pressure		Inflated Overall Diameter (mm)	Inflated Section Width (mm)	Pattern Depth (mm)	Pattern	Operative Norm
					Dual(Kg/Kpa)	Single(Kg/Kpa)					
215/75R17.5	14	126/124	L/M	6.00	1600/700	1700/700	767	212	13.0	BFL986	ETRTO
215/75R17.5	16	135/133	J/L	6.00	2060/850	2180/850	767	212	13.0	BFL986	ETRTO





BFL960

- Special design for all position of buses and steer and trailer axle of trucks.
- Good side-wear resistance.
- High-speed performance.



Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load and Inflated Pressure		Inflated Overall Diameter (mm)	Inflated Section Width (mm)	Pattern Depth (mm)	Pattern	Operative Norm
					Dual(Kg/Kpa)	Single(Kg/Kpa)					
10.00R20	16	146/143	L	7.5	2725/830	3000/830	1054	278	15.0	BFL960	TRA
10.00R20	18	149/146	K	7.5	3000/930	3250/930	1054	278	15.0	BFL960	GB
11.00R20	16	150/147	L	8	3075/830	3350/830	1085	293	16.0	BFL960	GB
11.00R20	18	152/149	L	8	3250/930	3550/930	1085	293	16.0	BFL960	TRA
11.00R22	16	152/149	K	8	3250/830	3550/830	1135	293	15.0	BFL960	TRA
11.00R22	18	154/151	K	8	3450/930	3750/930	1135	293	15.0	BFL960	TRA
12.00R20	18	154/151	L	8	3450/830	3750/830	1125	315	16.0	BFL960	TRA
295/80R22.5	16	150/147	M	9	3075/830	3350/830	1044	298	16.5	BFL960	GB
305/75R24.5	16	154/149	L	9	3250/850	3750/850	1080	305	15.0	BFL960	ETRTO
305/75R24.5	14	152/148	L	9	3150/800	3550/800	1080	305	15.0	BFL960	ETRTO





BFL820

- Suitable for all position of buses and the steer and trailer axle of trucks running on the highway.



Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load and Inflated Pressure		Inflated Overall Diameter (mm)	Inflated Section Width (mm)	Pattern Depth (mm)	Pattern	Operative Norm
					Dual(Kg/Kpa)	Single(Kg/Kpa)					
8.5R17.5	12	121/120	M	6.00	1400/625	1450/625	802	215	13.5	BFL820	ETRTO
205/75R17.5	14	124/122	M	6.00	1500/750	1600/750	753	205	13.0	BFL820	ETRTO
225/70R19.5	12	125/123	M	6.75	1550/660	1650/660	811	226	13.0	BFL820	TRA
225/70R19.5	14	128/126	M	6.75	1700/760	1800/760	811	226	13.0	BFL820	TRA
245/70R19.5	12	129/127	M	7.50	1750/660	1850/660	839	248	13.5	BFL820	TRA
245/70R19.5	14	133/131	M	7.50	1950/760	2060/760	839	248	13.5	BFL820	TRA
245/70R19.5	14	133/131	M	7.50	1950/750	2060/750	839	248	13.5	BFL820	ETRTO
245/70R19.5	16	136/134	M	7.50	2120/825	2240/825	839	248	13.5	BFL820	ETRTO
245/70R19.5	16	136/134	□	7.50	2120/825	2240/825	839	248	13.5	BFL820	ETRTO
255/70R22.5	14	136/133	M	7.50	2060/700	2240/700	930	255	14.5	BFL820	ETRTO
255/70R22.5	16	140/137	M	7.50	2300/830	2500/830	930	255	14.5	BFL820	TRA
265/70R19.5	14	136/134	M	7.50	2120/725	2240/725	867	262	14.0	BFL820	ETRTO
265/70R19.5	16	140/138	L	7.50	2360/775	2500/775	867	262	14.0	BFL820	ETRTO
265/70R19.5	18	143/141	J	7.50	2575/850	2725/850	867	262	14.0	BFL820	ETRTO
275/70R22.5	16	148/145	M	8.25	2900/900	3150/900	958	276	15.0	BFL820	ETRTO
275/70R22.5	16	144/141	M	8.25	2575/830	2800/830	958	276	15.0	BFL820	□B
285/70R19.5	16	144/142	M	8.25	2650/800	2800/800	895	283	14.5	BFL820	/
285/70R19.5	18	146/144	M	8.25	2800/900	3000/900	895	283	14.5	BFL820	ETRTO
285/70R19.5	18	150/147	J	8.25	3075/900	3350/900	895	283	14.5	BFL820	/





BDR900

- Suitable for drive axle of trucks running under an wide range of use, from highway to light unpaved road.



Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load and Inflated Pressure		Inflated Overall Diameter (mm)	Inflated Section Width (mm)	Pattern Depth (mm)	Pattern	Operative Norm
					Dual(Kg/Kpa)	Single(Kg/Kpa)					
12R22.5	16	152/148	L	9.00	3150/850	3550/850	1084	300	22.0	BDR900	ETRTO
12R22.5	18	152/149	L	9.00	3250/930	3550/930	1085	300	22.0	BDR900	GB
295/80R22.5	16	152/148	M	9.00	3150/850	3550/850	1044	298	20.5	BDR900	ETRTO
315/80R22.5	18	154/150	M	9.00	3350/825	3750/825	1076	312	22.0	BDR900	ETRTO
315/80R22.5	20	156/150 (154/150)	L(M)	9.00	3350/850	4000/850	1076	312	22.0	BDR900	ETRTO
315/70R22.5	16	154/150 (152/148)	L(M)	9.00	3350/900	3750/900	1014	312	20.0	BDR900	ETRTO
315/60R22.5	16	152/148	L	9.75	3150/900	3550/900	950	313	19.5	BDR900	ETRTO





BDO901

■ Suitable for drive axle of trucks under all kinds of working conditions.



Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load and Inflated Pressure		Inflated Overall Diameter (mm)	Inflated Section Width (mm)	Pattern Depth (mm)	Pattern	Operative Norm
					Dual(Kg/Kpa)	Single(Kg/Kpa)					
11R22.5	16	146/143	L	8.25	2725/830	3000/830	1054	279	20.5	BDO901	TRA
11R22.5	16	148/145	L	8.25	2900/850	3150/850	1054	279	20.5	BDO901	ETTRO
11R24.5	16	149/146	L	8.25	3000/830	3250/830	1104	279	22.5	BDO901	TRA
295/80R22.5	16	152/148	L	9.00	3150/850	3550/850	1044	298	20.5	BDO901	ETTRO
295/80R22.5	18	152/149	L	9.00	3250/900	3550/900	1044	298	20.5	BDO901	GB

