

ROYALBLACK



POWER TO GO

LONG HAUL

PRODUCT MANUALS



RS201

Position: All Position

- High density, flexomatic blading, for outstanding braking on wet surfaces combined with high mileage.
- Groove bottom protectors help deliver additional defense against stone drilling.
- More mileage and greater lateral stability.

Size	RIM	P.R.	Pattern	L.I/S.R.	Max load(kg)		S.W. mm	O.D. mm	T.D. mm
	inch				Single	Dual			
9.5R17.5	6.75	14	RS201	129/127L	1850	1750	232	836	12.5
215/75R17.5	6.00	16	RS201	127/124M	1750	1600	211	767	12
215/75R17.5	6.00	18	RS201	135/133J	2180	2060	211	767	12
235/75R17.5	6.75	16	RS201	132/130M	2000	1850	233	797	12.5
235/75R17.5	6.75	18	RS201	143/141J	2725	2575	233	797	12.5
225/70R19.5	6.75	14	RS201	128/126M	1800	1700	226	811	12.5
245/70R19.5	7.50	16	RS201	136/134M	2180	2060	248	839	12.5
265/70R19.5	7.50	16	RS201	140/138M	2500	2360	260	862	12.5
285/70R19.5	8.25	16	RS201	146/144M	3000	2800	282	886	13
285/70R19.5	8.25	18	RS201	150/148J	3150	2900	282	886	13
255/70R22.5	7.50	16	RS201	140/137M	2500	2300	254	920	11
275/70R22.5	8.25	16	RS201	148/145M	3150	2900	216	952	14.5
315/70R22.5	9.00	20	RS201	154/150M	3750	3350	312	1014	15
385/55R22.5	12.25	20	RS201	160L	4500	4500	383	996	15.5
295/75R22.5	9.00	16	RS201	146/143M	3000	2725	298	1014	15.5
295/80R22.5	9.00	18	RS201	154/151M	3550	3250	298	1044	15.5
315/80R22.5	9.00	20	RS201	157/154M	4125	3750	312	1076	15.5
385/65R22.5	11.75	20	RS201	160L	4500	4500	389	1071	15.5
11R22.5	8.25	16	RS201	148/145M	3150	2900	268	1054	14.5
12R22.5	9.00	18	RS201	152/149M	3550	3250	300	1075	14.5
11R24.5	8.25	16	RS201	149/146M	3250	3000	279	1104	14.5
285/75R24.5	8.25	14	RS201	144/141M	2800	2575	283	1050	15.5
285/75R24.5	8.25	16	RS201	147/144M	3075	2800	283	1050	15.5

LONG HAUL

PRODUCT MANUALS



RD808

Position: Drive Position

- Extra deep tread with stone drilling protectors to promote long original mileage.
- Optimised bead area construction for better durability.
- Closed-shoulder tread design provides even wear while maintaining excellent traction.

Size	RIM	P.R.	Pattern	LJ/S.R.	Max load(kg)		S.W. mm	O.D. mm	T.D. mm
	inch				Single	Dual			
11R22.5	8.25	16	RD808	148/145M	3150	2900	268	1054	20
295/75R22.5	9.00	16	RD808	148/143K	3000	2725	298	1014	20
11R24.5	8.25	16	RD808	149/146K	3250	3000	279	1104	20
285/75R24.5	8.25	16	RD808	147/144L	3075	2800	283	1050	20

MINING

PRODUCT MANUALS

RS600

Position: All Position

- Latest technology carcass geometry and materials for enhanced damage resistance, durability and loading capacity.
- Premium Zigzag design promotes soft soil mobility.
- Offset block shoulder design with SILICA compound promotes good traction and abrasion resistance.



Size	RIM	P.R.	Pattern	L./S.R.	Max load(kg)		S.W.	O.D.	T.D.
	inch				Single	Dual			
7.50R16	6.00G	14	RS600	122/118L	1500	1320	215	800	13
8.25R16	6.50H	16	RS600	128/124K	1800	1600	225	848	11.5
8.25R20	6.5	16	RS600	139/137K	2430	2300	234	970	15
9.00R20	7.0	16	RS600	144/142K	2800	2650	260	1018	15.5
10.00R20	7.5	18	RS600	149/146K	3250	3000	278	1051	16.5
11.00R20	8.0	18	RS600	152/149K	3550	3250	288	1079	16
12.00R20	8.5	18	RS600	154/151K	3750	3450	309	1115	16.3
12.00R20	8.5	20	RS600	156/153K	4000	3650	309	1115	16.3
11R22.5	8.25	16	RS600	148/145M	3150	2900	268	1054	14.5
12R22.5	9.00	18	RS600	152/149M	3550	3250	300	1075	14.5
13R22.5	9.75	20	RS600	156/150L	3750	3450	320	1124	15.5
11R24.5	8.25	16	RS600	149/146M	3250	3000	279	1104	14.5
12.00R24	8.5	20	RS600	160/157K	4500	4125	315	1226	15
315/80R22.5	9.00	20	RS600	156/150M	4000	3350	312	1076	14.5
295/80R22.5	9.00	18	RS600	152/149M	3550	3250	298	1044	14.5

ROYALBLACK