

STARSTONE



2019
version 1.0

TRUCK AND BUS

TYRE CATALOG



SHANDONG HABLEAD RUBBER CO.,LTD

📍 No.262 Qingken Road, Dawang Rubber Industry Area Guangrao, Shandong, China

☎ 0546-6871788 ✉ durungoldwaytire@sina.com

🌐 www.habileadchina.com

STARSTONE

CONTENTS
TRUCK AND BUS TYRE

02.....	INTRODUCTION
04.....	YTH1
05.....	YTH2
06.....	YTH3
07.....	YTH4
08.....	YTH6
09.....	YTH7
10.....	YTH8
11.....	YTH10
12.....	YTH12
13.....	YTH13
14.....	YTH18
15.....	YTH19
16.....	YT102
17.....	YT902
18.....	YT903
19.....	YT906
20.....	YT907
21.....	YT908
22.....	YT909
23.....	YT919





INTRODUCTION

Shandong Habilead Rubber Co., LTD. It is located in the coast of the Bohai Sea, the Yellow River Blue Economic Area center city --Dongying city, superior position, and convenient transportation. It is a large enterprise that combined PCR and TBR research development, manufacture, sale, independent import and export trade. Habilead insist to be better and perfect, focus on the introduction of advanced technology and high-end equipment, develop and produce high-grade precision and sophisticated products, creating a road of product differentiation. The main brands are DURUN, GOLDWAY, BANNERS, and HABLEAD. DURUN brand is awarded "China well-known trademark" by the state trademark bureau.

Habilead will be adhering to the business philosophy of "market-oriented, customer-centric, technology-supported"; With the development path of "talent-enterprises, science and technology enterprises, quality first", Habilead will provide high-quality, high-performance products to all customer as its responsibility and develop by the road of "excellent quality, leading the future".





YTH1

Suitable for various road conditions

YTH2

Suitable for high way and regional road conditions




Wear-resisting formula


Classic 3 grooves design

Designed for different complicated conditions




Wear-resisting formula



Continuous fire shoulder prevents irregular wear
4 grooves design provides good drainage performance



Size	PR	SS	Standard Rim	LI	Tread Depth
7.50R16LT	12	K	6.00G	120/118	11.5
7.50R16LT	14	K	6.00G	122/118	11.5
8.25R16LT	14	K	6.90H	126/122	11.5
8.25R16LT	16	K	6.90H	128/124	11.5
8.25R20	14	K	8.5	136/134	12.5
8.25R20	16	K	8.5	136/137	12.5
9.0R20	14	K	7.8	141/138	13.5
9.0R20	16	K	7.8	144/142	13.5
10.00R20	16	K	7.8	146/143	14.5
10.00R20	18	K	7.5	149/148	14.5
11.00R20	16	K	8.8	150/147	16.5

Size	PR	SS	Standard Rim	LI	Tread Depth
11.00R20	18	K	8.8	152/148	16.5
12.00R20	18	K	8.5	154/151	16.5
12.00R20	20	K	8.5	156/153	16.5
12.00R24	18	K	8.5	158/155	15.0
12.00R24	20	K	8.5	160/157	15.0
315S32G2.5	18	L	9.00	154/151	16.5
315S32G2.5	20	L	9.00	156/156	16.5
12R22.5	16	L	9.00	150/147	14.5
12R22.5	18	L	9.00	152/149	14.5

Size	PR	SS	Standard Rim	LI	Tread Depth
9.00R20	14	K	7.8	141/139	15.0
9.00R20	16	K	7.8	144/142	15.0
10.00R20	16	K	7.5	140/143	17.0
10.00R20	18	K	7.5	148/146	17.0
11.00R20	16	K	8.8	150/147	17.0
11.00R20	18	K	8.8	152/149	17.0
11R22.5	14	K	8.25	144/142	17.0
11R22.5	16	K	8.25	148/143	17.0
16R22.5	14	L	7.59	141/139	15.0
16R22.5	16	L	7.59	144/142	15.0



YTH3

Suitable for normal road condition and middle distance

YTH4

Suitable for high way condition and long distance



Optimized bead and belt structure make a strong tire body
Super wide section provides driving stability and long mileage
The combination of transverse and longitudinal pattern makes a good balance of traction and handling



Continuous tire shoulder prevents irregular wear
Special protrusions at the bottom of grooves avoid groove crack and clamping stones
Multi-directional sipes on tread provide good heat dissipation and ensure the long mileage




Size	PR	SS	Standard Rim	LI	Tread Depth
9.00R20	14	K	7.0	141/139	15.0
9.00R20	16	K	7.0	144/142	15.0
10.00R20	16	K	7.5	146/143	16.0
10.00R20	18	K	7.5	149/146	16.0
11.00R20	16	K	8.0	150/147	16.5
11.00R20	18	K	8.0	152/149	16.5
12.00R20	18	K	8.5	154/151	16.5
12.00R20	20	K	8.5	156/153	16.5
12R22.5	16	L	9.00	150/147	14.5
12R22.5	18	L	9.00	152/149	14.5
10R22.5	14	L	7.50	141/139	15.0
10R22.5	16	L	7.50	144/142	15.0

Size	PR	SS	Standard Rim	LI	Tread Depth
215/75R17.5	16	J	6.80	130/133	12.5
225/70R19.5	12	M	6.75	129/125	12.5
225/70R19.5	14	M	6.75	128/126	12.5
235/75R17.5	16	J	6.75	143/141	12.5
245/70R19.5	16	J	7.50	135/133	12.5
255/70R22.5	16	J	7.50	140/137	12.5
265/70R19.5	14	J	7.50	137/134	12.5
265/70R19.5	16	J	7.50	143/141	12.5
275/70R22.5	16	J	8.25	144/141	14.5
275/70R22.5	16	J	8.25	146/145	14.5
11R22.5	14	K	8.25	144/142	14.5
11R22.5	16	K	8.25	146/143	14.5
11R24.5	14	K	8.25	146/143	14.5
11R24.5	16	K	8.25	149/146	14.5
295/75R22.5	14	K	9.00	144/141	14.5
295/70R22.5	16	K	9.00	140/143	14.5
285/75R24.5	14	K	8.25	144/141	14.5
285/75R24.5	16	K	8.25	147/144	14.5



YTH6

Suitable for high way and regional road conditions


 High mileage assured with super deep tread
 Lateral blocks provide excellent traction power
 Special protrusions at the bottom of grooves avoid groove crack and clamping stones



YTH7

Suitable for high way condition


 Compact pattern design provides longer mileage
 Continuous tire shoulder prevents irregular wear
 4 straight grooves bring great steering performance



Size	PR	SS	Standard Rim	LI	Tread Depth
11R22.5	14	K	8.25	144/142	21.5
11R22.5	16	K	8.25	146/143	21.5
11R24.5	14	K	8.25	146/143	21.5
11R24.5	16	K	8.25	149/146	21.5
295/75R22.5	14	K	9.00	144/141	21.5
295/75R22.5	16	K	9.00	146/143	21.5
285/75R24.5	14	K	8.25	144/141	21.5
285/75R24.5	16	K	8.25	147/144	21.5

Size	PR	SS	Standard Rim	LI	Tread Depth
12R22.5	16	L	9.00	150/147	14.5
12R22.5	18	L	9.00	152/149	14.5
295/80R22.5	16	L	9.00	150/147	14.5
295/80R22.5	18	L	9.00	152/149	14.5
13R22.5	16	K	9.75	152/149	14.5
315/80R22.5	18	L	9.00	154/151	14.5
315/80R22.5	20	L	9.00	156/150	14.5



YTH8

Suitable for high way and regional road conditions

YTH10

Suitable for high way condition




Wear-resisting formula


High mileage assured with super deep tread
Lateral blocks provide excellent traction power



Continuous tire shoulder prevents irregular wear
Special protrusions at the bottom of grooves avoid groove crack and clamping stones
Multi-directional sipes on tread provide good heat dissipation and ensure the long mileage



Size	PR	SS	Standard Rim	LI	Tread Depth
295/80R22.5	16	L	9.00	150/147	21.5
295/80R22.5	18	L	9.00	152/149	21.5
315/80R22.5	18	L	9.00	154/151	22.5
315/80R22.5	20	L	9.00	156/150	22.5
12R22.5	16	L	9.00	150/147	17.0
12R22.5	18	L	9.00	152/149	17.0
11R22.5	14	K	8.25	144/142	22.5
11R22.5	16	K	8.25	146/143	22.5
11.00R20	16	K	8.0	150/147	17.0
11.00R20	18	K	8.0	152/149	17.0

Size	PR	SS	Standard Rim	LI	Tread Depth
385/65R22.5	20	K	11.75	180	15.0



YTH12

Suitable for high way condition

YTH13

Suitable for high way condition



Continuous tire shoulder prevents irregular wear
 Irregular sequence pattern pitch design reduces noise efficiently
 Multi-directional sipes on tread provide good heat dissipation and ensure the long mileage



Continuous tire shoulder prevents irregular wear
 Special protrusions at the bottom of grooves avoid groove crack and clamping stones
 Multi-directional sipes on tread provide good heat dissipation and ensure the long mileage



Size	PR	SS	Standard Rim	LI	Tread Depth
12R22.5	16	L	9.00	150/147	15.0
12R22.5	18	L	9.00	152/149	15.0

Size	PR	SS	Standard Rim	LI	Tread Depth
12R22.5	16	L	9.00	150/147	15.0
12R22.5	18	L	9.00	152/149	15.0



YTH18

Suitable for high way and regional road conditions



Continuous tire shoulder prevents irregular wear
3 grooves design provides good drainage performance and driving stability



Size	PR	SS	Standard Rim	LI	Tread Depth
11R22.5	14	K	8.25	144/142	16.5
11R22.5	16	K	8.25	146/143	16.5
12R22.5	16	L	9.00	150/147	16.5
12R22.5	18	L	9.00	152/149	16.5



YTH19

Suitable for high way and regional road conditions



High mileage assured with super deep tread
Lateral blocks provide excellent traction power



Size	PR	SS	Standard Rim	LI	Tread Depth
11R22.5	14	K	8.25	144/142	18.5
11R22.5	16	K	8.25	146/143	18.5
12R22.5	16	K	9.00	150/147	19.5
12R22.5	18	K	9.00	152/149	19.5



YT102

Suitable for high way condition

YT902

Suitable for on-off road conditions



 **Wear-resisting formula**



Continuous tire shoulder prevents irregular wear
Irregular sequence pattern pitch design reduces noise efficiently



 **Anti-puncture formula**



Ultra strong structure provides excellent high load capacity
Football pattern design and deep groove bring excellent traction and braking ability



Size	PR	SS	Standard Rim	LI	Tread Depth
7.00R16LT	10	L	5.50F	111/107	
7.00R16LT	12	L	5.50F	115/110	
7.50R20	12	L	6.0	128/126	
7.50R20	14	L	6.0	130/128	

Size	PR	SS	Standard Rim	LI	Tread Depth
11.00R20	16	K	8.0	150/147	18.5
11.00R20	18	K	8.0	152/149	18.5
12.00R20	18	K	8.5	154/151	20.0
12.00R20	20	K	8.5	156/153	20.0

YT903

Suitable for on-off road conditions



Anti-puncture formula



Lateral blocks provide excellent traction power
Arc-shape groove design provides good drainage performance



Anti-puncture formula



Big strong block design improves the off-road ability
Unique pattern design brings excellent driving and braking ability



Size	PR	SS	Standard Rim	LI	Tread Depth
11.00R20	16	K	8.0	150/147	18.5
11.00R20	18	K	8.0	152/149	18.5
12.00R20	18	K	8.5	154/151	19.5
12.00R20	20	K	8.5	156/153	19.5

Size	PR	SS	Standard Rim	LI	Tread Depth
7.50R16LT	12	E	6.00G	120/116	18.5
7.50R16LT	14	D	6.00G	122/118	18.5
8.25R16LT	14	E	6.50H	126/122	18.5
8.25R16LT	16	D	6.50H	128/124	18.5
8.25R20	14	E	6.5	136/134	18.5
8.25R20	16	D	6.5	139/137	18.5
10.00R20	16	E	7.5	146/143	25.2
10.00R20	18	D	7.5	149/146	25.2
11.00R20	16	E	8.0	150/147	25.2
11.00R20	18	D	8.0	152/149	25.2
12.00R20	18	E	8.5	154/151	25.2
12.00R20	20	D	8.5	156/153	25.2

YT907

Suitable for on-off road condition and short distance


Anti-puncture formula



Lateral blocks provide excellent traction power

Special protrusions at the bottom of grooves avoid groove crack and clamping stones



YT908

Suitable for mix road condition


Anti-crack formula



Lateral blocks provide excellent traction and braking power

Ultra strong structure provides excellent high load capacity



Size	PR	SS	Standard Rim	LI	Tread Depth
7.50R16LT	12	K	6.00G	120/116	14.5
7.50R16LT	14	K	6.00G	122/118	14.5
8.25R16LT	14	K	6.50H	126/122	14.5
8.25R16LT	16	K	6.50H	128/124	14.5
8.25R20	14	K	6.5	136/134	14.5
8.25R20	16	K	6.5	138/137	14.5
9.00R20	14	K	7.0	141/139	16.5
9.00R20	16	K	7.0	144/142	16.5
10.00R20	16	K	7.5	146/143	17.5
10.00R20	18	K	7.5	149/146	17.5
11.00R20	16	K	8.0	150/147	18.5
11.00R20	18	K	8.0	152/149	18.5
12.00R20	18	K	8.5	154/151	18.5
12.00R20	20	K	8.5	156/153	18.5

Size	PR	SS	Standard Rim	LI	Tread Depth
9.00R20	14	K	7.0	141/139	17.5
9.00R20	16	K	7.0	144/142	17.5
10.00R20	16	K	7.5	146/143	18.5
10.00R20	18	K	7.5	149/146	18.5
11.00R20	16	K	8.0	150/147	19.5
11.00R20	18	K	8.0	152/149	19.5
12.00R20	18	K	8.5	154/151	19.5
12.00R20	20	K	8.5	156/153	19.5



YT909

Suitable for on-off road conditions and short distance

YT919

Suitable for mix road condition



T
Anti-puncture formula



Lateral blocks provide excellent traction power
Big strong block design improves the off-road ability

Special protrusions at the bottom of grooves avoid groove crack and clamping stones



T
Anti-puncture formula



Lateral blocks provide excellent traction power
Big strong block design improves the off-road ability

Special protrusions at the bottom of grooves avoid groove crack and clamping stones



Size	PR	SS	Standard Rim	LI	Tread Depth
11R22.5	16	J	8.25	148/145	22.00
12R22.5	18	F	9.00	152/149	23.20
12.00R20	20	F	8.50	156/153	24.20

Size	PR	SS	Standard Rim	LI	Tread Depth
12.00R20	18	F	8.5	154/151	23.2
12.00R20	20	F	8.5	156/153	23.2
11.00R20	16	F	8.0	150/147	23.2
11.00R20	18	F	8.0	152/149	23.2
9.00R20	14	F	7.0	141/139	19.0
9.00R20	16	F	7.0	144/142	19.0